

Size
36"
A0 (91.4cm)



HP DESIGNJET T2500PS eMFP Series

EPrinter baru dirancang, dua-roll, dan web-terhubung dengan scan dan dapat menyalin

akiraDATA[®]
Deliver Technology to Your Business

6 Colour



Architecture
Engineering
and Construction



Infrastructure
Utilities and
Telecommunications



Education



Manufacturing
Automotive
and Transportation



Public sector
and Corporate



Retail

Pengalaman pengguna yang inovatif

- Menghilangkan kekacauan output - Dapatkan datar, cetakan tersusun rapi berkat integrasi output stacking tray.
- Kendali penuh - memantau roll media, lihat status printer pada layar sentuh, dan memantau pekerjaan selama proses percetakan.
- Memuat dua gulungan kertas dengan mudah- bahkan ketika duduk dengan front loading dan automatic paper-roll alignment.
- Mencetak hingga A0/E dengan tersusun rapat, printer 36 inci yang dirancang dengan permukaan datar untuk cepat memeriksa hasilcetak.

Print, scan, dan salinan dengan satu perangkat

- Mempercepat alur kerja Anda — dengan mudah memindai dan e-mail sketsa dan anotasi gambar tangan langsung ke partners Anda¹.
- Langsung berbagi dan mengelola konten-memindai folder jaringan, FTP, USB drive, atau langsung ke awan.
- Meningkatkan waktu — mencetak beberapa pekerjaan di berbagai jenis media dan ukuran dengan 2 roll terpisah dan smart switching.
- Buat ukuran cetakan A1/D dalam 21 detik — tinta asli HP memberikan hitam pekat dan abu-abu netral yang benar.

Cetak secara virtual dari manapun²

- Gunakan smartphone Apple[®], Android[™] atau Tab Anda untuk mencetak secara virtual dimanapun¹.
- Akses dan cetak pekerjaan Anda dari cloud ketika berada di luar kantor menggunakan HP Designjet ePrint & Share¹.
- Menyimpan secara otomatis hasil salin pekerjaan Anda di Cloud, ketika anda mencetak menggunakan HP Designjet ePrint & Share¹.
- Mencetak tanpa driver menggunakan USB stick atau langsung kirim email untuk proyek Anda ke HP DesignJet T2500PS eMFP^{1,2}.

Eco Highlights

- Help save paper with automatic print settings and image nesting
- Less ink wasted due to efficient installation and maintenance routines
- Free, convenient HP ink cartridge and printhead recycling¹
- Works with FSC[®]- and PEFC[™]-certified HP papers²

¹ Program availability varies. Please check hp.com/recycle for details.
² FSC[®] trademark license code FSC[®]-C017543, see fsc.org. PEFC[™] trademark license code PEFC[™]/29-31-198, see pefc.org. Not all FSC[®]- or PEFC[™]-certified products are available in all regions.

Please recycle large-format printing hardware and printing supplies.

Find out how at our website
hp.com/ecosolutions



¹ Requires an HP DesignJet ePrint & Share account, Internet connection to the printer, and connected Internet-capable device. When using the HP DesignJet ePrint & Share mobile app, a compatible Apple[®] iOS or Android[™] device and Internet connection are required. Data or connection charges may apply. Print times may vary. For more information, visit hp.com/go/eprintandshare.

² Scanning of PDF files only available with HP DesignJet T2500 PostScript[®] eMultifunction Printer.

³ Only files in TIFF, JPEG and PDF format can be e-mailed with a size limit of 10 MB.

PRINTER SPECIFICATIONS

Print	Line drawings ⁴	21 sec/page on A1/D, 120 A1/D prints per hour
	Print resolution	Up to 2400 x 1200 optimized dpi
	Margins (top x bottom x left x right)	Roll: 5 x 5 x 5 mm (0.2 x 0.2 x 0.2 in) (borderless on photo roll media) Sheet: 5 x 22 x 5 x 5 mm (0.2 x 0.87 x 0.2 x 0.2 in)
	Technology	HP ThermalInkjet
	Ink types	Dye-based (C, G, M, pK, Y); pigment-based (mK)
	Ink drop	6 pl (C, M, Y, G, pK); 9 pl (mK)
	Printheads	1 (C, G, M, mK, pK, Y)
	Line accuracy	+/- 0.1% ⁵
	Minimum line width	0.02 mm (0.0008 in) (HP-GL/2 addressable)
	Guaranteed minimum line width	0.07 mm (0.0028 in) (ISO/IEC 13660:2001(E)) ⁶
Media	Handling	Input: two automatic front-loading roll feeds, smart roll switching, sheet feed; Output: integrated output stacking tray (from A4/A to A0/E, with up to 50 A1/D-size capacity), media bin, automatic cutter Scanner: straight-through scan paper path for sheet and cardboard originals
	Size	Rolls: 279 to 914 mm (11 to 36 in) Sheets: 210 x 279 to 914 x 1219 mm (8.3 x 11 to 36 x 48 in) Standard sheets: A4, A3, A2, A1, A0 (A, B, C, D, E)
	Thickness	Up to 0.5 mm (19.7 mil)
Scan	Scan speed	Color: up to 3.81 cm/sec (1.5 in/sec) Grayscale: up to 11.43 cm/sec (4.5 in/sec)
	Scan/copy resolution	Up to 600 dpi
	Maximum scan	Size: 914 x 8000 mm (36 x 315 in) (JPEG) 914 x 5000 mm (36 x 197 in) (PDF) 610 x 15,000 mm (24 x 590.5 in) (TIFF) Thickness: 0.8 mm (0.03 in)
Copy	Reduction/enlargement	25 to 400%
	Maximum copies	Up to 99 copies
	Copier settings	Copy quality, copy color roll, content type, original paper type, background removal, contrast, de-skew, blueprints support
Memory Connectivity⁸	128 GB (virtual) ⁹ , 320 GB hard disk	
	Interfaces (standard)	Gigabit Ethernet (1000 Base-T) supporting the following standards: TCP/IP, BootP/DHCP (IPv4 only), DHCPv6, TFTP (IPv4 only), SNMP (v1, v2, v3), Apple Bonjour Compatible, FTP, WS Discovery, Embedded Web Server (HTTP, HTTPS), IPsec, SMTP (Notification Alerts), Raw IP printing (9100, 9101, 9102), LPD, IPP, WS print, NTLmV1 (Scan to network folder), SSL/TLS 1.0, 802.1X authentication (LEAP, PEAP, EAP-TLS).
	Print languages (standard)	PostScript [®] eMultifunction Printer: Adobe PostScript 3, Adobe PDF 1.7 Extension Level 3, HP-GL/2, HP-RTL, TIFF, JPEG, CALS G4, HP PCL 3 GUI, URF
	Printing paths	Printer driver, HP DesignJet ePrint & Share, HP Embedded Web Server, HP Instant Printing, direct printing from USB flash drive, email printing
	Drivers (included)	HP-GL/2, HP-RTL drivers for Windows [®] ; HP PCL 3 GUI driver for Mac OS X; PostScript Windows, Linux, and Mac drivers ⁵
Dimensions (w x d x h)	Printer	1399 x 916 x 1110 mm (55.1 x 36.1 x 43.7 in)
	Shipping	1502 x 759 x 825 mm (59.1 x 29.9 x 32.5 in)
Weight	Printer	112 kg (245 lb)
	Shipping	137.5 kg (303.1 lb)
What's in the box	HP DesignJet T2500 eMultifunction Printer, printhead, introductory ink cartridges, stacking tray, printer stand and media bin, spindles, quick reference guide, setup poster, startup software, power cord	
Environmental ranges	Operating temperature:	5 to 40°C (41 to 104°F)
	Storage temperature:	-25 to 55°C (-13 to 131°F)
	Operating humidity:	20 to 80% RH
Acoustic	Sound pressure: 47 dB(A) (printing); 39 dB(A) (ready); <16 dB(A) (sleep)	
	Sound power: 6.5 B(A) (printing); 5.8 B(A) (ready); <1.9 B(A) (sleep)	
Power consumption	< 120 watts (printing), < 260 watts (maximum), < 4 watts (< 7 watts with embedded Digital Front End) (sleep), 0.1 watts (auto-off), 0 watts (off hard switch)	
	Input voltage (auto ranging) 100 to 240 VAC (+/- 10%), 50/60 Hz (+/- 3 Hz), 4.2 A max (peak current)	
Certification	Safety	USA and Canada (CSA certified), EU (LVD and EN 60950-1 compliant), Russia (GOST), Singapore (PSB), China (CCC), Argentina (IRAM), Mexico (NYCE), Korea (KATS)
	Electromagnetic	Compliant with Class A requirements, including: USA (FCC rules), Canada (ICES), EU (EMC Directive), Australia (ACMA), New Zealand (RSM), China (CCC), Japan (VCCI); Certified as Class A product: Korea (KCC)
	Environmental	ENERGY STAR, WEEE, EU RoHS, China RoHS, REACH, FEMP, EPEAT Bronze
Warranty	One-year limited hardware warranty	

ORDERING INFORMATION

Product	CR359A	HP DesignJet T2500 36-in PostScript eMultifunction Printer	
Accessories	CN538A	HP DesignJet 3-in Core Adapter	
	L4R66A	HP DesignJet 36-in Spindle	
	B3P06A	HP 727 DesignJet Printhead	
Original HP printhead	B3P17A	HP 727 40-ml Photo Black DesignJet Ink Cartridge	
Original HP ink cartridges	B3P13A	HP 727 40-ml Cyan DesignJet Ink Cartridge	
	B3P14A	HP 727 40-ml Magenta DesignJet Ink Cartridge	
	B3P15A	HP 727 40-ml Yellow DesignJet Ink Cartridge	
	B3P18A	HP 727 40-ml Gray DesignJet Ink Cartridge	
	C1Q11A	HP 727 69-ml Matte Black DesignJet Ink Cartridge	
	B3P23A	HP 727 130-ml Photo Black DesignJet Ink Cartridge	
	B3P19A	HP 727 130-ml Cyan DesignJet Ink Cartridge	
	B3P20A	HP 727 130-ml Magenta DesignJet Ink Cartridge	
	B3P21A	HP 727 130-ml Yellow DesignJet Ink Cartridge	
	B3P24A	HP 727 130-ml Gray DesignJet Ink Cartridge	
	B3P22A	HP 727 130-ml Matte Black DesignJet Ink Cartridge ¹⁰	
	C1Q12A	HP 727 300-ml Matte Black DesignJet Ink Cartridge	
	HP large format printing materials	B1011	BIMA White Plan Paper 80-85gr 24" x 50m (A1)
		B1111	BIMA Tracing Paper / Kalkir 80-85gr 24" x 50m (A1)
		B1211.1	PAPERCAD Premium Tracing Paper / Kalkir 90-95gr 24" x 50m (A1)
B1311		BIMA Matte Drafting Film 75 Micron 24" x 40m (A1)	
B1511		PAPERCAD White Film 220gr 24" x 30m (A1)	
B1812		PAPERJET Premium Glossy Photo Paper 260gr WTP 24"x30m	
B1913		PAPERJET Premium Silky Photo Paper Water Proof 260gr 24" x 30m	
B1012		BIMA White Plan Paper 80-85gr 36" x 50m (A0)	
B1112		BIMA Tracing Paper / Kalkir 80-85gr 36" x 50m (A0)	
B1212.1		PAPERCAD Premium Tracing Paper / Kalkir 90-95gr 36" x 50m (A0)	
B1312		BIMA Matte Drafting Film 75 Micron 36" x 40m (A0)	
B1512		PAPERCAD White Film 220gr 36" x 30m (A1)	
B1813		PAPERJET Premium Glossy Photo Paper 260gr WTP 36"x30m	
B1914		PAPERJET Premium Silky Photo Paper Water Proof 260gr 36" x 30m	
Service and support		U0MD9E	HP 3 year Next Business Day Onsite Support ¹³
	U0ME3E	HP 3 year 4-hour response, 9x5 Onsite Support ¹³	
	U0ME4E	HP 3 year 4-hour response, 13x5 Onsite Support ¹³	
	U0ME7E	HP 3 year Next Business Day Onsite Support with Defective Media Retention ¹⁵	
	U0ME9PE	HP 1 year Post Warranty Next Business Day Onsite Support ¹³	
	U0MF4PE	HP 1 year Post Warranty Next Business Day Onsite Support with Defective Media Retention ¹⁵	
	U0MF3PE	HP 1 year Post Warranty 4-hour response, 13x5 Onsite Support ¹³	

HP DesignJet Support Services offer solutions for business critical environments — installation, extended support and maintenance, as well as variety of value added services. For more information, please visit hp.com/go/DesignJetsupport.

Use Original HP inks and printheads to experience consistent high quality and reliable performance that enable less downtime. These critical components are designed and engineered together as an optimized printing system to provide precise line accuracy as well as dark blacks and true neutral grays¹⁵. For more information, visit hp.com/go/OriginalHPinks.

For the entire HP Large Format Printing Materials portfolio, please see HPLFMedia.com.

Mechanical printing time. Printed in Fast mode, using HP Bright White Inkjet Paper (Bond) and Original HP inks. +/-0.1% of the specified vector length or +/-0.2 mm (whichever greater) at 23°C (73°F), 50-60% relative humidity, on A0/E Matte Film in Best or Normal mode with Original HP inks.

Measured on HP Matte Film.
Based on 1.5 GB RAM.
Includes an embedded Jetdirect print server.
Included with PostScript[®] printers only.

¹⁰ Available only in Europe, Middle East, and Africa.

¹¹ FSC[®] trademark license code FSC[®]-C017543, see fsc.org. PEFC[™] trademark license code PEFC[™]/29-31-198, see pefc.org. Not all FSC[®]- or PEFC[™]-certified products are available in all regions.

¹² Can be recycled through commonly available recycling programs.

¹³ Not available in North America and Latin America.

¹⁴ Not available in Europe, Middle East, and Africa.

¹⁵ Applicable to HP DesignJet T-series Printers, ePrinters, and eMFPs. True neutral grays produced by printers compatible with the HP Three-black ink set.



Partnership :



www.akiradata.co.id



Call Center
021-830 3894



marketing
@akiradata.co.id

HEAD OFFICE & SHOWROOM

Jl. Dr. Saharjo No. 105C
Tebet – Jaksel 12860
Telp. (021) 830 3894 Fax. (021) 829 5777
E-mail : marketing@akiradata.co.id

SERVICE CENTER

Jl. Persada Raya No. 43
Tebet Jakarta Selatan
Telp. (021) 829 9059